



XV-5080 Compatibility Guide

Current Operating System: 1.12

Memory

SIMMS should be 72pin, 16/32/64MB, 5v, FPM or EDO, 60ns or faster, with a height of 36mm or less. SmartMedia cards should be 3.3v or 5v, 2-128MB. We recommend using the highest quality SIMM's and memory cards possible. The following SIMMs have been tested successfully with the XV-5080:

Delkin		K-Tech Devices		Buffalo	
SM072-032P5244-7	32MB	MD64E72A60	64MB	VMH-64LS(EDO)	32MB x 2 pcs.
SM072-064E5464-6	64MB	MD32E72A60	32MB	Logitec	
Green House		MD32NP72A60	32MB	LSM-32A6(FP)	32MB
GH-32E16MA/60-64	64MB	MD16E72A60	16MB	LSM-32A6x2EDO(EDO)	32MB
GH-S3216MA/60-64	64MB	MD16NP72A60	16MB	Princeton	
GH-S328MA/60	32MB			PD72E-64	64MB
GH-32E8MA/60	32MB				
GH-32E4MA/60	16MB				

External Drives

Most SCSI, SCSI II, and Ultra SCSI compatible drives will work with the XV-5080. The following drives have been tested successfully with the XV-5080:

CD-ROM	NEC	CDR500	Zip	lomega	Zip 100
	Matshita	KME 07			Zip 250
	Plextor	PX-40TS	Jaz	lomega	Jaz 1GB
	Toshiba	XM-5301TA	Orb	Castlewood	ORB 2.2GB
		XM-3701TA	DVD-RAM	Matshita	LF-D102
	Pioneer	DR-U24X	PD	Matshita	LF-1600
		PCP-PR1	MO	Necitsu	MOF-640
		PCP-PR2	HDD	Quantum	Fireball 1080S
		PCP-PR24		I-O Data	HDVS-UM8.4G
CD-R	Matshita	CW-7501		Necoda	240NZ
CD-RW	JVC	XR-W2042		Melco	DSC-UE series
	Plextor	PX-W4220T			

Contact Sources

Rackmount SCSI Drives:	Phone	Desktop SCSI Drives:	
Glyph Technologies	(800) 335-0345	APS	(800) 925-4922
Rorke Data	(800) 328-8147	MacWarehouse	(800) 645-9173
SoundLogic	(760) 789-6558		
Memory		3rd Party	
Delkin	(800) 637-8087 x141	CD-ROM Distributors	
Epoch	(800) 736-3762	East-West Soundwarehouse	(800) 833-8339
Think Computer Products	(800) 726-2477 x128	Ilio Entertainment	(800) 747-4546
SoundLogic	(760) 789-6558	NorthStar	(503) 760-7777
		Q Up Arts	(800) 454-4563
		SampleHeads	(800) 807-6056
		Spectrasonics	(800) 764-9379